## 







 $CPX \ 4160B \text{ is a } 16 \times 12 \text{ watts outdoor RGBW LED wash bar. With an IP65 rating,} a robust built and 16 bright LEDs controlled in 8 sections, this LED bar is the solution for any architectural, stage and events applications.}$ 

SOURCE	Light source: 16 x 12 watts RGBW LED, 4 in 1 RGBW LEDs LED life expectancy: 50,000 Hrs.	Dimensions
	Beam angle: 40° Light output: 2500 Lux @ 2m @ 40°	1968. <del>7</del> 3
	Dimmer: 4 selectable dimming curves Color mixing: RGBW Strobe and fade effect Built-in color and dynamic macros	84.66 ↓ → ↓
	Control protocols: DMX, Master-Slave, Auto Run Display : TFT displayer with 4 buttons Control channels: 1, 4, 7, 11, 19, 32, 35 CHs	140
ELECTRICAL	Input voltage: 100-240V/50-60Hz Power consumption: 128 watts	Luminous Diagram
CONNECTIONS	DMX connections: IP DMX In/Out cables with 3 pin screw lock connectors Power connections: IP power In/Out cable, 3 pin screw lock connectors	(m) 4 2
PHYSICAL	Dimensions: 1068.73 x 84.66 x 140mm Net weight: 5.5 Kg Housing: Aluminum IP rating: 65 Operating temperature: -20°C/45° C	40" 2 0 0 2 4 6 8 10