



THEATRICAL

FR 40C is designed for short distance wash. It is a super compact, easy for setup LED Fresnel powered by 40 watts 5600K daylight LED. Featuring 25 to 90° zoom, 95 CRI, 90 R9, rotary control of dimmer. It delivers a smooth, soft and flat field of light. A barn door is included to shape the light.

SOURCE Light source: 40 watts Cool white COB LED
Color temperature: 5600K
LED life expectancy: 50,000 Hrs

OPTICAL SYSTEM Manual zoom
Zoom range: 25° to 90°
Light output: 14,000 Lux @ 1m @ 25°

PHOTOMETRICS CRI (Color Rendering Index) : >95; R9>90
CQS (Color Quality Scale): >96
TM-30 Rf (IES TM-30-15 Fidelity Index): >92
TM-30 Rg (IES TM-30-15 Gamut Index): >98
TLCI (Television Lighting Consistency Index): >98



KEY FEATURES 5 Dimmer curves
Strobe
Video flicker free
PMMA polymethyl methacrylate lens
Barn doors included

CONTROL & PROGRAMMING Control protocols: Rotary, DMX, RDM
Control channels: 1, 2, 3, 4 CHs

ELECTRICAL CONNECTIONS Input voltage: AC100-240V/50-60Hz
DMX Connections: 3 pin XLR In/Out male and female
Power connections: PowerCon In/Out

PHYSICAL Dimensions: 230 x 156 x 279mm
Net weight: 1.7 Kg (barn door included)
Color: Black
Housing: Aluminum
IP rating: 20; Operating temperature: -5°C/45°C

Dimensions



Luminous Diagram

