









 $PR\ 300C$ is a 5600K Cool white LED Profile powered by a 300 watts COB LED. It's designed to substitute the traditional 1 KW Tungsten Halogen lamp profile. It delivers a flat and even field of light, crisp pattern projection and high CRI of 97. An optional high performance Fresnel lens with barn doors can replace the profile lens offering an even Fresnel wash from the same LED engine. This LED profile offers the flexibility and high quality output required to stand out in theatres, studios and events applications.

SOURCE: Light source: 300 watts Cool white COB LED

Colortemperature: 5600K LED life expectancy: 50,000 Hrs

CRI: 97, R9 ≥ 90 TLCI: 98

OPTICAL: Manual zoom **SYSTEM**: Zoom range: 18° to 38°

Light output: 29,000 Lux @ 2m @ 18° Optional Fresnellens adapter 25°-50° (PMMA)

Optional Iris and Gobo holder

KEY: 5 Dimmer curves FEATURES: 16 bit dimmer

Strobe

Video flicker free with selectable PWM

Intelligent temperature control

Silent operation

CONTROL & : Control protocols: Rotary, DMX, RDM PROGRAMMING: Control channels: 1, 2, 3 CHs

ELECTRICAL: Input voltage: AC100-240V/50-60Hz

CONNECTIONS: DMX connections: 3 pin and 5 pin XLR In/Out male and female

Power connections: PowerCon In/Out


PHYSICAL: Dimensions: 745 x 294 x 294mm


Netweight: 8.7 Kg (including lens)

Color: Black IP rating: 20

Operating temperature: -5°C/45°C

Dimensions





Luminous Diagram

