

# CYCLOPS LIGHTING



**SPR 328R** is a 1U 19" Rack mounted RDM/DMX Splitter. It buffers, multiplies, isolates and protects console DMX outputs. It features 2 independent RDM/DMX inputs/thru and 8 optically isolated RDM/DMX outputs, where each can be assigned to one of the two inputs giving flexibility in data distribution.

**FEATURES**

- Bi-directional communication and data transfer
- Split and boost the RDM/DMX signal
- Power and data optically isolated RDM/DMX ports
- High voltage protection
- Selectable input source for each RDM/DMX output
- High brightness Power and RDM Status LED indicators
- Individual input selection LED indicators per output
- Front panel Power on/off switch

**CONTROL & PROGRAMMING**

- RDM/DMX Pass-Thru
- Input selector switches
- Power on/off switch
- Power and Data LED indicators

**CONNECTIONS**

- Data inputs: 2 x Neutrik 3 pin XLR
- Data thru: 2 x Neutrik 3 pin XLR
- Data outputs: 8 x Neutrik 3 pin XLR
- Power input: Neutrik powerCon
- Power output: Neutrik powerCon

**ELECTRICAL**

- Input Voltage: AC 88-256V 50/60 Hz
- Power consumption: ??

**PHYSICAL**

- Dimensions: 482 x 118 x 46 mm
- Net Weight: 1.7 Kg
- Color: Black

## Dimensions

