









SPARKLY LED 1000P is an extremely powerful 1000 watts LED moving head profile with four rotatable shutter blades. It features a CMY color mixing, a set of static and interchangeable rotatable gobos and a rotatable prism for a wide variety of patterns and designs. In addition to the loaded dynamic features, it offers a wide zoom range from 6 to 39 degrees, Iris and a CTO filter (3200-6000K) making it the versatile and perfect fit moving head profile for theatrical and studio applications, as well as concerts and band events.

SOURCE Light source: 1000 watts white LED

LED life expectancy: 20000 Hrs.

CRI > 75 (High CRI > 85 SKU: SparklyLED1000PH)

OPTICAL SYSTEM Beam angle: 6° to 39°

Four shutter blades, 180° rotatable

Electronic focus

150mm diameter front lens

DYNAMIC Dimmer: 0-100% linear adjustment

Color mixing: CMY **EFFECTS**

Color wheel: 7 colors + white CTO filter, 3200K to 6000K Static gobo: 8 gobos + open Rotating gobo: 6 gobos + open

Prism: 4 facet prism

Frost

CONTROL & Control protocols: DMX, Master-Slave, Auto Run

PROGRAMMING ECO Mode

Display: 3.5' color LCD display, reversible 180°

Control channels: 37, 41 CHs

MOVEMENT Pan: 540°

Tilt: 270°

Resolution: 16 bit

ELECTRICAL Input voltage: 110-240V/50-60Hz

Power consumption: 1300 watts

DMX connections: 3 pin/5 pin XLR In/Out male and female CONNECTIONS

Power connections: Powercon In

PHYSICAL Dimensions: 482 x 372 x 870 mm

Net weight: 42 Kg Color: Black IP rating: 20





