



**PIXIBARPRO 48-OS** is a RDM Outdoor IP66 LED Pixel Bar with 48 RGB LEDs and 16 Pixels control. It delivers a dynamic and smooth color mixing and pixel effect with a square opal diffuser cover. It comes with an alignment bar for a straight and seamless edge to edge installation and accepts a M10 size bolt for clamp attachment making it ideal for both permanent architectural installation and temporary rental stage and events.

**SOURCE** Light source: SMD3535 RGB LEDs  
LED quantity: 48 LEDs

**OPTICAL SYSTEM** Cover: Square opal diffuser  
View angle: 165°

**CONTROL & PROGRAMMING** Pixels control: 16  
Color mixing: RGB  
Control protocols: RDM, DMX  
Control channels: 48 CHs  
Address setting: RDM, Manual

**ELECTRICAL** Input voltage: 24V  
Power consumption: 10 watts / per meter

**CONNECTIONS** Power and data connection: 15cm 5 pin male/female cable  
Cable entry: Bottom

**PHYSICAL** Dimensions: 1000 x 28 x 46 mm (without bracket)  
Color: Silver  
Material: Aluminum 6063 with UV Protection  
Operating temperature: -30°C/50°C  
Humidity: 0-90%  
IP rating: 66

## Dimensions

